

EonServ 4012/ EonServ 4016

Easy Management for Entry-level Storage Server

• System hardware advantage

The all-in-one design of EonServ is cable-less and easy to maintain with modular components.

• Data safety

Protected by Infortrend RAID technology, users can be rest assured the safety of their stored data from accidental or mechanical errors.

• Intuitive design

EonOne Lite's one-button-per-page design is intuitive and easy to use.

No complicated setup processes, have the system up and running ASAP!

| | | | |
|-------------------------|--|-----------------------------|---|
| Form factor | 2U 12-bay/3U 16-bay | Service port | Service port x 1 |
| Controller architecture | Single controller | | (mini USB connector - RS 232 interface) |
| System drive | Support Two 2.5" SATA HDD (optional) | PCI-E Gen3 slot | PCI-E 3.0 x 8 slot x 2 or PCI-E 3.0 x16 slot x 1 |
| CPU | Default • Intel Core i3-4330, dual-core 3.5G | Drive interface | 6Gb/s SATA |
| | Upgradables • Intel Xeon E3-1225, quad-core 3.2G | Disk support | • 3.5" 7,200 RPM SATA HDD |
| | • Intel Xeon E3-1275, quad-core 3.5G | Compatible Operating System | • Windows 7 Professional SP1, 64-bit |
| DIMM slot | DDR3 slot x 4 | | • Windows Server 2012, 64-bit |
| Memory capacity | Default: 8GB(2 x 4GB) with non-ECC | Installation | • Windows 7 Embedded Standard SP1, 64-bit |
| | Upgradable to 8GB(2 x 4GB) with ECC | RAID Functionality | • Linux Ubuntu 13.04 |
| | 16GB(2 x 8GB) with ECC or non ECC | PSU | OS can be installed in backend 2.5" SATA system drive |
| | 32GB(4 x 8GB) with ECC or non ECC | Enclosure Dimension | RAID 0, 1, 5, 6, 10, 50, 60 |
| Rear I/O ports | • RJ-45 Gigabit Ethernet x 4 (default) | | Single PSU (500 watts) |
| | • USB 2.0 x 2 | | 2U 19-inch rackmount with chassis ears: |
| | • USB 3.0 x 2 | | (H)88.00mm x (W)447.40mm x (L)524.41mm |
| | • VGA x 1 | | 3U 19-inch rackmount with chassis ears: |
| | • HDMI x 2 | | (H)130.00mm x (W)447.40mm x (L)524.20mm |
| | • Mic. in port x 1 | | |
| | • Speaker out port x 1 | | |
| | • Digital IO: 8 x Input, 2 x Output | | |

* All design and specification declared are subject to change without notice in advance.
All rights reserved. Please refer to Infortrend website for further information or localization updates.

Asia Pacific (Taipei, Taiwan)
Infortrend Technology, Inc.

Tel: +886-2-2226-0126
E-mail : sales.ap@infortrend.com

China (Beijing, China)
Infortrend Technology, Ltd.

Tel: +86-10-6310-6168
E-mail : sales.cn@infortrend.com

Japan (Tokyo, Japan)
Infortrend Japan, Inc.

Tel: +81-3-5730-6551
E-mail : sales.jp@infortrend.com

Americas (Sunnyvale, CA, USA)
Infortrend Corporation

Tel: +1-408-988-5088
E-mail : sales.us@infortrend.com

EMEA (Basingstoke, UK)
Infortrend Europe Ltd.

Tel: +44-1256-305-220
E-mail : sales.eu@infortrend.com